

zenithinteriors.com

UMBRA Round Acoustic Light

Zenith

Features:

An impressive acoustic lighting luminaire that lights up anything from conferences room to communal dining spaces. As the long, rounded silhouette suspends from the ceiling, it creates an intimate atmosphere and contributes a sheltering feeling of home along with an extra touch of cosy.

Design: IMPACT ACOUSTIC

Options:

- Acoustic panel booster made of felt for additional acoustic absorbtion.

Environmental:

- Cradle to Cradle Certified™
- Product qualifies for LEED v4 specifications on VOC emissions in LEED EQ credit
- SUPPORTED BY CLIMATE KIC

Warranty: 12 year product & 2 year lighting

Finishes:



100% PET (min. 60% post-consumer)

ARCHISONIC® is a high-performance sustainable acoustic absorber made from up-cycled plastic bottles.

ARCHISONIC® is manufactured at the highest quality standards, yet slight colour and surface deviations caused by the high degree of recycled fiber are an inevitable part of the product characteristics and do not claim warranty services.

Material varies in colour when shown in monitor or in print.

ARCHISONIC:

| | | | | | |
|---|--|---|---|---|---|
|  |  |  |  |  |  |
| Shell Pink 102 | Jute 920 | Soft Coral 516 | Ice Blue 304 | Winter Sky 410 | Spearmint 706 |
|  |  |  |  |  |  |
| Succulent 712 | Pacific Ocean 432 | Marine Blue 864 | Deep Sea 918 | Midnight 810 | True Navy 194 |
|  |  |  |  |  |  |
| Moss 439 | Grove 317 | Nordic Pine 311 | Fern 180 | Sunshine 846 | Honeycomb 139 |
|  |  |  |  |  |  |
| Terracotta 239 | Electric Orange 464 | Hot Pink 140 | Poster Red 662 | Grape 540 | Garnet 724 |
|  |  |  |  |  |  |
| Warm Stone 105 | Linen 107 | Lichen 160 | Snow White 500 | Cloud 103 | Milk 404 |
|  |  |  |  |  |  |
| Gull 144 | Smoke 442 | Ground 108 | Slate 444 | Charcoal 542 | Raven 550 |



Sound Absorption:

DIN ISO 11654
24 mm


- aw 0.55 (no airgap)
- aw 0.65 (50 mm / 2" air gap)
- aw 0.90 (100 mm / 4" air gap)
- aw 0.95 (200 mm / 8" air gap)
- aw 0.95 (300 mm / 11" air gap)

Key Data:

- Voltage: 220 - 240 V
- Power: 19W
- Luminus flux: 1580lm
- Protection class: IP 20 / protection class I
- Colour consistency: SDCM 3
- Life span: >50'000 h (L70 B50)
- Dimming: DALI
- Colour temperature: 4000K




Dimensions




Round 400

Dia 400mm
OH 270mm
Thickness: 24mm




Round 600

Dia 600mm
OH 400mm
Thickness: 24mm




Round 800

Dia 800mm
OH 530mm
Thickness: 24mm



Round 1200

Dia 1200mm
OH 650mm
Thickness: 24mm



Round 1600

Dia 1600mm
OH 850mm
Thickness: 24mm