

Features:

Verse 3 brings a spacious meeting area with heightened privacy features to your workplace, fully complying with DDA regulations. It fosters a calm setting, reducing workplace noise for discussions and minimizing disruptions caused by private conversations. It's equipped with acoustic elements, air ventilation, and adjustable lighting for comfortable collaboration. Its leveling system ensures it stays balanced with the floor.

Championing their sustainability commitment, Crafted Hardwoods will contribute to reforestation through OneTreePlanted for each Verse purchased with Crafted Hardwoods frames, For every Verse 3 sold, 3 trees will be planted.

Options:

- Media panel can house 42" 65" TV and can be placed with a wall mounted table at sitting or standing height
- 4 standard room sizes (WxD) with 2 available heights
- Door handle left or right side
- White board or cork board accessories
- 600W or 900W SOL-EDT lounges

Design: ZENITH DESIGN STUDIO

Warranty: 5 years (Refer to Zenith Warranty Document for details)

Certifications: GECA, 3 Green Star Credits for acoustics

Finishes:

Finisnes:		
Frame:	Victorian Ash Timber, Crafted	
	Hardwood Timber Tasmanian Oak &	
	Blackbutt (Converted low value,	
	juvenile pulp turned into new	
	hardwoods that look and feel like	
	100-year-old wood)	
Front Wall Panel:	Laminated Glass 6.76mm	
Glazed Door:	Frameless Toughened Glass 10mm	
	(Center only)	
Internal Side Walls:	Fabric or Sonic Board	
Internal Back Walls:	Laminated Glass 6.76mm, Fabric or	
	Sonic Board	
External Side Walls:	Fabric	
External Back Walls:	Laminated Glass 6.76mm or Fabric	
Ceiling Internal:	Sonic Board	
Ceiling External:	Natural White Matt Laminate	
Inner/Outer Floor Track: Black - Satin ZPC_001		
Upholstery in fabric categories A, B, C, D & E		
Refer to Verse Fabric Specification		

Frame:



Sonic Board:








Milky White ZPET_009

Dimensions:



 Verse 3.1

 OW 2880mm


 OD 1980mm

 H 2200/2400mm (Frame)

 OH 2370/2600mm (Including fan box)

 Internal Room Size: 2700 x 1800mm

Side walls made up of: 3x 600mmW panels Front & back walls made up of: 3x 900mmW panels




Verse 3.3

OW 2880mm

- OD 2580mm
- H 2200/2400mm (Frame)
- OH 2370/2600mm (Including fan box)
- Internal Room Size: 2700 x 2400mm

Side walls made up of: 1x 600mmW & 2x 900mmW panels Front & back walls made up of: 3x 900mmW panels




Verse 3.2

OW 2880mm OD 2280mm

H 2200/2400mm (Frame)

OH 2370/2600mm (Including fan box) Internal Room Size: 2700 x 2100mm

Side walls made up of: 2x 600mmW & 1x 900mmW panels Front & back walls made up of: 3x 900mmW panels




Verse 3.4

- OW 2880mm
- OD 2880mm
- H 2200/2400mm (Frame)
- OH 2370/2600mm (Including fan box)
- Internal Room Size: 2700 x 2700mm

Side Walls made up of: 3x 900mmW panels Front & back walls made up of: 3x 900mmW panels


Accessories:




White Board or Cork Board with Black or Dark Brown Leather Strap DIA: 600 & 900mm



Gallery Rail White board or cork board are easily attached and relocated



SOL-EDT 600 OW 588mm OD 690mm SD 490mm SH 450mm OH 817mm




SOL-EDT 900 OW 888mm OD 690mm SD 490mm SH 450mm OH 817mm


Back Panel (Internal) Options:




Option 1 All Glass



Option 2 All Fabric or Sonic Board Panels




Option 1A Glass with Media Panel



Option 2B All Fabric or Sonic Board Panels with Media Panel


Front Panel Options:



Option 1

LH: Glass Panel

- RH: Glass Panel
- C: Door Panel
- LH: Door Hinges




Option 2

LH: Glass Panel RH: Glass Panel C: Door Panel


RH: Door Hinges

Media Panel:



Standing Height


Media Panel 900mmW: Optional Wall Mounted Table Fabric or Sonic Board (Internal) Table Height: 1050mm Table Width: Max 900mmW TV Bracket Height: 1520mm (Eye Level) TV Size: 42" - 65" Note: TV & TV bracket not included



Sitting Height

Media Panel 900mmW: Optional Wall Mounted Table Fabric or Sonic Board (Internal) Table Height: 720mm Table Width: Max 900mmW TV Bracket Height: 1175mm (Eye Level) TV Size: 42" - 65" Note: TV & TV bracket not included

GPO Panel:




Left Hand Side

Panel: 600/900mmW

- Al: 1175mmH
- A2: 945mmH
- B1: 805mmH
- B2: 605mmH
- B3: 165mmH

Right Hand Side Mirrored

Power Outlet Options:



Note: *not available as a power outlet option when a media panel has been selected.

Acoustics:


Verse has been tested in accordance with ISO 717-1:2004 Acoustics – Rating of sound insulation in buildings and of building elements – Airborne sound insulation.

Independent Acoustic Testing shows that Verse can qualify for 3 Green Star Credits for acoustics and can achieve between 28-36Dw at 40dB Ambiance with a Privacy Rating of 64-74, depending on the wall type and material selected.

Normal voice conversations can be heard as a muffled sound in adjoining rooms but cannot be understood.

Verse acoustic performance is comparable to most general use office rooms.

Panel Layers:



Air Ventilation:

Verse 3 has Induction airflow to give the larger room cleaner and better air exchange, with a maximum rating of 100L/s for 5 people in the space.



Fire Safety:

The fire safety of all surface materials; timber, upholstery and acoustics materials used in Verse are tested and classified by either national or international standards.

No fire hazardous materials are used in the construction. Timber frames use BAL-19 Victorian Ash with natural fire resistance qualities (Higher rated Blackbutt BAL-29 can be used on request). Upholstered frame MDF substrate meets AS 3837, AS 1859.2 & AS 4266.16. Fabrics used in upholstery meets AS 3837 & ISO 5660-1. Interior and roof Sonic Boards meets EN 13501-1; B-s1,d0. Roof and wall acoustic insulation meets ISO 9705 & AS 5637.1. Laminate boards used in the roof meets AS 1859.2/3, AS 4266.13, AS 1539.3, and AS 3837.

The installation or relocation of Verse is not allowed to adversely impact on the regulatory requirements of a building. The location of Verse has to consider the location of exits and paths of travel to exists so as to not restrict the use or access of them.

Verse roof is adaptable to sprinklers and smoke detectors. Check with your local experts on the specific regulations, however if fire sprinklers are required in the booths a flexible pipe is to be used and at least 100mm of clearance above the ceiling to enable the roof to be lifted to gain access to services in the ceiling.

Lighting:

Verse comes with 19W/m LED Strip Lighting and Driver suited for different room sizes with 1800lm/m Natural White (4000K).

Verse lighting brightness can be controlled by a dimmer, and turned off by PIR sensor when the room is unoccupied.

Door / Light Switch Position:

All lighting components are compliant with Asia Pacific regional standards and certification requirements that include, EN 60598-1&2, AS61347.1&2, RCM, CE, RoHs and CCC.

|--|--|

Panel: 600/900mmW Floor Height: 1050mm Depth from Left/Right Side: 500mm Central external swing door Switch can be placed on left hand or right hand front panel

Seismic Safety:

Verse can be anchored to the floor with bolts to keep the room upright in case of seismic activity. On request only. If Seismic is required, then depending on local Electrical Regulations alternative wiring looms may be required. Contact us for more information.

Zenith |